



32 Mechanic Avenue Unit 211 • Woonsocket RI 02895

Tel. 401-767-2269

401-767-2255

www.microsorbtech.com

E-mail: engineer@microsorbtech.com

**Product
Bulletin**

A-40

**MICROSORB RF
ABSORBER PAINT**

GENERAL DESCRIPTION

MICROSORB FR is used for coating Microsorb foam based absorber products. FR dries to a flat finish and is available in a range of colors.

Microsorb FR Paint is a latex paint with special additives to enhance its fire retardancy.

SPECIFICATIONS

Colors: Blue, White

Also available in other colors.

APPLICATION

MICROSORB FR coverage is approximately 400 square feet per gallon (10 square meters per liter). FR dries in a half hour and additional coats may be applied in 2 to 4 hours. Do not apply FR at temperatures below 50°F (10°C).

Stir thoroughly with a circular lifting motion. Thinning is not recommended, but if necessary, use water sparingly. Use adequate ventilation when spraying.

SIZES

MICROSORB FR is available in gallon and five gallon pails.

Please contact your **MICROSORB** Customer Service Department to discuss your specific requirements.

Warranty: This information is, to the best of Microsorb Technologies knowledge, accurate as of the date indicated. This information relates only to the specific materials designated herein and is not intended for the application or use of the materials with any other materials or in any process. The information is intended as a general guide only and does not constitute a warranty or representation whatsoever and MICROSORB TECHNOLOGIES HEREBY DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES ARISING FROM THE USER'S RELIANCE ON OR USE OF THIS INFORMATION.